



## PET Backlit Film - TAG Digital®

### TECHNICAL DATA SHEET

#### Description:

The **PET Backlit film - TAG Digital®** is designed for backlit applications such as light boxes, bus shelters,...

#### Characteristics:

The **PET Backlit film - TAG Digital®** has a thickness of 200 $\mu$  and is available in matte and glossy versions.

#### Durability:

The maximum recommended duration of use is 1 year.

#### Storage:

1 year between 15 and 25°C and 45 to 55% humidity in the original box.

#### Product references:

<b>PET Backlit 200<math>\mu</math> Matt</b>	<b>1,27 x 30 m</b>	PETM-BACK-200-127030
	<b>1,27 x 50 m</b>	PETM-BACK-200-127050
	<b>1,37 x 30 m</b>	PETM-BACK-200-137030
	<b>1,37 x 50 m</b>	PETM-BACK-200-137050
	<b>1,52 x 30 m</b>	PETM-BACK-200-152030
	<b>1,52 x 50 m</b>	PETM-BACK-200-152050
<b>PET Backlit 200<math>\mu</math> Glossy</b>	<b>1,27 x 30 m</b>	PETG-BACK-200-127030
	<b>1,27 x 50 m</b>	PETG-BACK-200-127050
	<b>1,27 x 100 m</b>	PETG-BACK-200-127100
	<b>1,37 x 30 m</b>	PETG-BACK-200-137030
	<b>1,37 x 50 m</b>	PETG-BACK-200-137050
	<b>1,37 x 100 m</b>	PETG-BACK-200-137100
	<b>1,52 x 30 m</b>	PETG-BACK-200-152030
	<b>1,52 x 50 m</b>	PETG-BACK-200-152050



Note:

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.