

Coated Frontlit PVC Banner - TAG Digital®

TECHNICAL DATA SHEET

Description:

The **Coated Frontlit PVC Banner - TAG Digital®** is a white banner specially designed for outdoor and indoor applications such as banners, signage, large format advertising and posters.

Characteristics:

The **Coated Frontlit PVC Banner - TAG Digital®** has a weight of 510 g/m². It is composed of a polyester fabric coated with white PVC, providing very good tensile strength as well as excellent weather and UV resistance.

Printing:

The **Coated Frontlit PVC Banner - TAG Digital®** can be printed with solvent, eco-solvent, latex and UV inks, offering excellent print quality and high color density.

Technical data:

Nylon fabric: 1000*1000D/20*20 sq.in

Tensile strength: 440/360 N/cm

Tear strength: 300/250 N

Temperature resistance: -10 to +70°C

Product references:

Coated Frontlit PVC Banner	1.05 x 50 m	COATBAN-510-105050
	2.50 x 50 m	COATBAN-510-250050
	3.20 x 50 m	COATBAN-510-320050

Note:

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.