

## Double-Sided PET Mounting Film 36 µm (Perm/Perm) - TAG Digital®

### TECHNICAL DATA SHEET



#### Description:

The **Double-Sided PET Mounting Film 36 µm (Permanent / Permanent) - TAG Digital®** is an ultra-clear PET film coated with a double-sided solvent-based permanent adhesive.

#### Characteristics:

The product consists of a 36 µm ultra-clear polyester film.

It is coated with ultra-clear solvent-based permanent adhesive on both sides, ensuring strong and long-lasting bonding.

It is supplied with a 23 µm PET liner, ensuring excellent transparency and stability during application.

#### Application guidelines:

Designed for permanent mounting applications on smooth and clean surfaces.

Ensure substrates are clean, dry and free of dust, grease or contaminants before application.

#### Durability:

The maximum recommended duration of use is 3 years.

#### Storage:

1 year when stored between 15°C and 25°C and at a relative humidity of 45 to 55% in the original packaging.

#### Product references:

<b>Double-Sided PET Mounting Film 36 µm (Perm/Perm)</b>	<b>1.07 x 50 m</b>	DSPET-036-P-P-107050
	<b>1.37 x 50 m</b>	DSPET-036-P-P -137050
	<b>1.52 x 50 m</b>	DSPET-036-P-P -152050

#### Note:

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.