

Monomeric PVC Floor Film 220 µm (R9) - TAG Digital[®]

TECHNICAL DATA SHEET

Description:

The **Monomeric PVC Floor Film 220 µm (R9) - TAG Digital[®]** is an anti-slip printable film designed for graphic applications on smooth indoor floors and walls such as concrete, tiles and stone surfaces.

Characteristics:

The product consists of a 220 µm white granular monomeric PVC film.

It is coated with a transparent removable adhesive, allowing clean removal after use.

It is supplied with a 140 g/m² PE-coated paper liner, ensuring good stability and handling.

Printing:

Compatible with solvent, eco-solvent, latex and UV inks.

Application guidelines:

Designed for application on clean, smooth indoor floor and wall surfaces.

Ensure the surface is dry, clean and free of dust, grease or contaminants before application.

Classification:

Anti-slip classification: R9

Durability:

The maximum recommended duration of use depends on application conditions and traffic intensity.

As a guideline:

High traffic areas (shopping centres, post offices, public spaces): up to 3 months

Medium traffic areas: up to 6 months

Low or occasional traffic: up to 12 months

Storage:

1 year when stored between 15°C and 25°C and at a relative humidity of 45 to 55% in the original packaging.

Product references:

Monomeric PVC Floor Film 220 µm (R9)	1.07 x 50 m	FLOOR-MPVC-220-107050
	1.37 x 50 m	FLOOR-MPVC-220-137050
	1.60 x 50 m	FLOOR-MPVC-220-160050

Note:

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.