

Polymeric PVC Floor Film 245 µm (R12) - TAG Digital®

TECHNICAL DATA SHEET

Description:

The **Polymeric PVC Floor Film 245 µm (R12) - TAG Digital®** is a non-slip printable film designed for graphic applications on indoor and outdoor floors and walls such as concrete, tiles and stone surfaces.

Characteristics:

The product consists of a 60 µm polymeric PVC film coated with an anti-slip surface layer, resulting in a total thickness of 245 µm.

It is coated with a permanent transparent adhesive, ensuring strong and durable bonding on various substrates.

It is supplied with a 120 g/m² paper liner, providing good handling and stability during application.

Printing:

Compatible with solvent, eco-solvent, latex and UV inks.

Application guidelines:

Designed for application on clean, smooth indoor and outdoor floor and wall surfaces.

Ensure the surface is dry, clean and free of dust, grease or contaminants before application.

Classification:

Anti-slip classification: R12

Fire classification: Euroclass Bfl-s1

Durability:

The maximum recommended duration of use depends on application conditions and traffic intensity.

As a guideline:

High traffic areas (shopping centres, post offices, public spaces): up to 3 months

Medium traffic areas: up to 6 months

Low or occasional traffic: up to 12 months

Storage:

1 year when stored between 15°C and 25°C and at a relative humidity of 45 to 55% in the original packaging.

Product references:

Polymeric PVC Floor Film 245 µm (R12)	1.27 x 30 m	FLOOR-PPVC-245-127030
--	--------------------	-----------------------

Note:

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.