

## **Lino Tex 1000 PVC Floor Covering - TAG Digital®**

### **TECHNICAL DATA SHEET**

#### **Description:**

The **Lino Tex 1000 PVC Floor Covering - TAG Digital®** is a white soft PVC foam floor covering reinforced with high-tenacity PES yarns. It is designed for indoor short- to medium-term applications such as exhibition stands, theatres and fashion shows.

#### **Characteristics:**

The product consists of a 2200 µm white soft PVC foam layer reinforced with a 100% PES high-tenacity fabric (300 x 300 denier), providing excellent visual appearance and mechanical strength.

With a total weight of 1000 g/m<sup>2</sup>, it offers high durability, good dimensional stability and strong resistance to tearing and tensile stress.

#### **Printing:**

Compatible with UV and latex inks.

The material provides good print quality and high colour density.

The printable side is located on the inside of the roll.

#### **Application guidelines:**

Designed for indoor floor covering applications such as exhibition stands, events and temporary installations.

Ensure the surface is clean, flat and free of dust before installation.

#### **Classification:**

Anti-slip classification: R10

Fire classification: Euroclass Bfl-s1

#### **Technical data:**

Weight: 1000 g/m<sup>2</sup>

Fabric: 100% PES 300 x 300D

Tensile strength: 650 / 550 N / 2.5 cm

Tear strength: 70 / 60 N

Service temperature: -20°C to +70°C

**Durability:**

The maximum recommended duration of use depends on application conditions and traffic intensity.

As a guideline:

High traffic areas: up to 3 months

Medium traffic areas: up to 6 months

Low or occasional traffic: up to 12 months

**Storage:**

1 year when stored in original packaging under normal indoor conditions.

**Product references:**

<b>Lino Tex 1000 PVC Floor Covering</b>	<b>1.60 x 15 m</b>	LINO-TEX-1000-160015
	<b>1.60 x 30 m</b>	LINO-TEX-1000-160030
	<b>2.20 x 30 m</b>	LINO-TEX-1000-220030
	<b>2.50 x 30 m</b>	LINO-TEX-1000-250030
	<b>3.20 x 30 m</b>	LINO-TEX-1000-320030

**Note:**

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.