



Coated Frontlit PVC Banner - TAG Digital®

TECHNICAL DATA SHEET

Description:

The **Coated Frontlit PVC Banner - TAG Digital®** is a white banner specially designed for outdoor and indoor applications such as stretched tarpaulins, signage, very large format advertising, posters, etc...

Characteristics:

The **Coated Frontlit PVC Banner - TAG Digital®** has a weight of 510 gr/m². It is composed of a polyester fabric coated with white PVC which gives it a very good tensile strength, weather and UV resistance.

Printing:

The **Coated Frontlit PVC Banner - TAG Digital®** can be printed with solvent, eco-solvent, latex and UV inks and offers a good printing rendering as well as a high color density.

Technical data:

Nylon fabric: 1000*1000D/20*20 sq.in

Tensile strength: 440/360 N/cm

Tear strength: 300/250 N

Temperature resistance: -10-70°C



Product references:

| | | |
|-----------------------------------|--------------------|--------------------|
| Coated Frontlit PVC Banner | 1,05 x 50 m | COATBAN-510-105050 |
| | 2,50 x 50 m | COATBAN-510-250050 |
| | 3,20 x 50 m | COATBAN-510-320050 |

Note:

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.