

Multilayer Blockout 340 μ Film R°-V° - TAG Digital

TECHNICAL DATA SHEET

Description:

Multilayer PVC-PET-PVC-PVC 340 μ Film printable R°/V°.

Characteristics:

The film is composed of four layers: Two identical super smooth outer sides allow a perfect printing result in high resolution on both sides.

This product is ideal for any use in Pop-up, X-banner, clip banner, displays, rigid posters...

Printing:

The product is printable in solvent, eco-solvent, UV, Latex and screen-printing inks.

Technical data:

Do not contact with products containing solvents or ammonia.

Tensile strength: 750 N/inch(L) – 692 N/inch(I)

Tear strength: 38 x 24 N

Product references:

PET Blockout 340μ	0,91 x 50 m	PET-BLOCK-340-091050
	1,07 x 50 m	PET-BLOCK-340-107050
	1,27 x 50 m	PET-BLOCK-340-127050

Note:

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.