

245µ PET Roll-up Grey Back - TAG Digital

TECHNICAL DATA SHEET

Description:

245µ (330 gr/m²) Multi-layers PET film with grey back for roll-up.

Characteristics:

The multilayer PET film is specially designed for roll-up. Its multi-layer composed of a core of 95µ transparent PET film covered on the front with a super opaque 75µ white welded PVC film and on the back with a grey welded 75µ 100% opaque PVC film, gives a very good stability and avoids the curling effect. Its super smooth surface allows a perfect printing result in high resolution.

This product is ideal for any use in Pop-up, X-banner, clip banner, displays, rigid posters...

Printing:

The product is printable in solvent, eco-solvent, UV, Latex and screen-printing inks.

Technical data:

Do not contact with products containing solvents or ammonia.

Tensile strength: 421N/inch

Tear strength: 24 x 19 N

Peeling strength: 23 N/inch

Product references:

PET for Rollup 245µ	0,91x50	ROL-PET-245-091050
	1,07x50	ROL-PET-245-107050
	1,27x50	ROL-PET-245-127050
	1,37x50	ROL-PET-245-137050
	1,52x50	ROL-PET-245-152050

Note:

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.