

Ultraclear PET Film - TAG Digital®



TECHNICAL DATA SHEET

Description:

The **Ultraclear PET Film - TAG Digital®** is designed for applications such as window posters, light boxes, bus shelters,...

Characteristics:

The **Ultraclear PET Film - TAG Digital®** has a thickness of 210 μ . It is coated on recto and has a static protective film on the back to protect the film during printing. Applications are various as product can be printed for example quadri mirror + white and be viewed from the back side with a uniform gloss finish.

Durability:

The maximum recommended duration of use is 3 years.

Ink Compatibility:

The product is printable in solvent, eco-solvent, UV, Latex and screen-printing inks.

Storage:

1 year between 15 and 25°C and 45 to 55% humidity in the original box.

Product references:

Ultraclear PET Film 210μ	1,27 x 50 m	PET-UC-210-127050
	1,37 x 50 m	PET-UC-210-137050

Note:

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.